

SSAK 6 | SSAK 6



086004-0-4

**SAMMELSCHIENENQUERSCHNITT |
EINSPEISUNG/
BUSBAR CROSS SECTION | INCOMING**

1 x Cu Sammelschienenstärke/
busbar strength (height) 3 -10 mm
Tiefe mindestens/
depth (width) minimum 10 mm

ABGANG/OUTGOING

2 x 1,5 - 6 mm²
1 - 4 mm²



086004-1-4



086004-2-4



086004-3-4



086004-4-4

Für Kupferleiter/For Copper Conductors (Cu)

NENNSPANNUNG/NOMINAL VOLTAGE

690 V AC

STROMBELASTBARKEIT/NOMINAL CURRENT

82 A

ZULASSUNG/STANDARDS

IEC 60947-7-1



AUSFÜHRUNG/MODEL	ARTIKEL-NR./PART NO.	TYP/TYPE	VPE/PU	GTIN/EAN
Kupferleiter Copper conductor	086004-0-4	SSAK 6 L G	12/96	4051589006279
	086004-1-4	SSAK 6 N	12/96	4051589006286
	086004-2-4	SSAK 6 PE	12/96	4051589006293
	086004-3-4	SSAK 6 L B	12/96	4051589006309
	086004-4-4	SSAK 6 L S	12/96	4051589006316

Abmessungen/Dimensions (mm)

