

UVB 200 - 1 POLIG



080030-0-X

EINSPEISUNG

1 x 70 - 10 mm²
50 - 6 mm²



- > Modularer Aufbau
- > Beliebig anreihbar
- > Montage auf DIN Schiene TS 35

ABGANG/BRÜCKE

1 x 35 - 4 mm²
25 - 2,5 mm²



ABGANG

6 x 16 - 1,5 mm²
10 - 1,5 mm²



AL / CU



080030-1-X



080030-2-X



080030-3-X



080030-4-X

Für Aluminium und Kupferleiter (Al/Cu)



NENNSPANNUNG

1000 V AC / 1500 V DC
1000 V AC / 1500 V DC

STROMBELASTBARKEIT

185 A Al
200 A Cu

ZULASSUNG

IEC 61238-1 (Class A)
IEC 60947-7-1



Ausführung	Artikel Nr.	Typ	VPE	GTIN / EAN
UVB 200 für Aluminium/ Kupferleiter	080030-0-3	UVB 200 L G	3/18	4051589003032
	080030-1-3	UVB 200 N	3/18	4051589003131
	080030-2-3	UVB 200 PE	3/18	4051589003230
	080030-3-3	UVB 200 L B	3/18	4051589003339
	080030-4-3	UVB 200 L S	3/18	4051589003438

Für Kupferleiter (Cu)



NENNSPANNUNG

1000 V AC / 1500 V DC

STROMBELASTBARKEIT

200 A

ZULASSUNG

IEC 60947-7-1



Ausführung	Artikel Nr.	Typ	VPE	GTIN / EAN
UVB 200 für Kupferleiter	080030-0-4	UVB 200 L G	3/18	4051589800303
	080030-1-4	UVB 200 N	3/18	4051589800310
	080030-2-4	UVB 200 PE	3/18	4051589800327
	080030-3-4	UVB 200 L B	3/18	4051589800334
	080030-4-4	UVB 200 L S	3/18	4051589800341

Abmessungen:

